



## Product

The EASY FOIL ST consists of a vapour permeable, coated fleece. Rain or powdery snow are retained by the film. The surface of the facade membrane ensures that driving rain and moisture run off the facade safely and reliably. The foil is supplied self-adhesive with a two or three part protective paper to simplify the application of the foil.

## Application examples

Air- and driving raintight finish for:

- Joinery (aluminium, wood, PU, PVC)
- Curtain walls
- Frames
- OSB
- Facade claddings
- Connections with our sealing films

## Colour foil

Black

## Widths, lengths and packaging

- 100 mm x 25 m (6 rolls/box)
- 150 mm x 25 m (4 rolls/box)
- 200 mm x 25 m (4 rolls/box)
- 250 mm x 25 m (2 rolls/box)
- 300 mm x 25 m (2 rolls/box)
- 350 mm x 25 m (2 rolls/box)
- 400 mm x 25 m (2 rolls/box)

## Advantages

- ✓ vapour open
- ✓ driving rain and windproof surface
- ✓ black surface
- ✓ very powerful, self-adhesive surface
- ✓ no construction adhesive required => very fast and cost-efficient installation
- ✓ self-adhesive performance largely built up after 60 minutes
- ✓ full adhesive strength achieved after approximately 3 days
- ✓ easy installation possible, even on difficult substrates

## For your information

The length tolerances of the foils are according to DIN 7715.  
Width tolerances : +/- 2.50 mm.

## Technical properties of the foil

Property	Value + unit
Product	coated fleece (smooth)
Weight (DIN EN 1849-2)	120 g/m <sup>2</sup> +/-10%
Fire class (DIN EN 13501)	E
Resistance to water penetration	W1
Water column testing (DIN EN 20811)	> 400 cm WS
μ <sub>d</sub> value	2 m +/- 0,50
UV resistance	9 months
Airtightness (DIN EN 12114)	< 0,01 m <sup>3</sup> /(h.m)
Aging test foil according to IFT guideline MO-01/1:1007 due to alternating tensile and compressive forces of ±100 kg/m <sup>2</sup> film.	passed V50 < 0,01 m <sup>3</sup> /(h.m)
Water tightness against driving rain (DIN EN 1027)	> 1200 Pa
Temperature resistance	-40°C to +80°C
Tensile strength (DIN EN 12311-2/A)	
• lengthwise	210 N/50 mm +/-30
• crosswise	140 N/50 mm +/-20
Elongation at break (DIN EN 12311-2/A)	
• lengthwise	110% +/-30
• crosswise	130% +/-30
Storage life	unlimited (*)

(\*) store in closed box, at room temperature (21°C and 50% relative humidity)

## Technical properties adhesive

Property	Value + unit
Adhesive	solvent-free acrylic dispersion
Adhesive carrier	polyester tissue
Weight	230 g/m <sup>2</sup>
Protective layer	PP-silicone foil
Thickness (without adhesive)	±0,23 mm
Adhesive strength [DIN EN 1939 (2003)]	≥ 35 N/25mm
Dynamic shear resistance (internal test)	≥ 15 N/cm <sup>2</sup>
Temperature resistance	-40°C to +100°C
Aging resistance	very good

# EASY FOIL ST

## Application

**Press very well with a pressure roller**  
**Maintain the roof tile principle**



## Remarks

The materials and substrate must be solid, grease-, oil- and dust-free. When applying the adhesive to e.g. joinery or non-porous surfaces, thoroughly degrease these substrates using the Dowsil™ R-40 cleaner and a soft, lint-free cloth.

The membrane may not be subjected to permanent loads, e.g. tensile or compressive forces. Before applying the foil, consult the processing guidelines.

Do not use for joints under joinery where there is a risk of standing water at the joint bond (e.g. balcony/terrace/skylight).

The product is not suitable for underground applications.

## Primer

On porous substrates (concrete, Ytong, etc.) an adhesive layer of 80mm is recommended. The adhesive strength strongly depends on the substrate and must be tested on each site in advance. If the adhesion is insufficient, the test must be repeated with CS-EPDM Foil Primer. In case of very moist / very absorbent substrates, the primer will greatly improve the adhesion. When bonding to EPDM or roofing, always use CS-EPDM Foil Primer and do a test in advance.

## Widths of the protective film of the adhesive layer :

- 100 mm : 30 mm + 70 mm
- 150 mm : 30 mm + 60 mm + 60 mm
- 200 mm : 30 mm + 85 mm + 85 mm
- 250 mm : 30 mm + 110 mm + 110 mm
- 300 mm : 30 mm + 135 mm + 135 mm
- 350 mm : 30 mm + 160 mm + 160 mm
- 400 mm : 30 mm + 185 mm + 185 mm

## Note

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 05-2018.

The producer reserves the right to make changes. 2024 10 15