



Product

Tape with UV-treated film coating with a very strong acrylic adhesive layer on 1 side.

Application examples

- sealing of roofs both inside and outside
- sealing of formwork
- airtight connection between vapour barriers
- taping of cracks between specific insulating plates

Colour

Black
White on demand

Thickness

0,30 – 0,33 mm (without protective paper)

Width

50 to 1.500 mm (every 5 mm)

Length

25 meter

Packaging

On a roll
In boxes, separated by a silicone paper

Protection of the adhesive

Brown siliconized paper

Advantages

- ✓ very good aging and moisture resistance
- ✓ can already be used from -10°C (dry surface)
- ✓ solvent-free adhesive layer

Remark

The materials and substrate must be dry, grease-free, oil-free, solid and dust-free.

Technical properties

Property	Value + unit
Adhesive carrier	LDPE film, black, 2 years UV resistance*, reinforced with a small net.
Adhesive	Acrylic dispersion
Protective paper	Brown siliconized paper
Thickness (without protective paper) (DIN EN 1942**)	0,30 – 0,33 mm
Adhesion (DIN EN 1939**)	≥ 30 N/25 mm
Elongation (DIN EN 14410**)	≥ 25 N/25 mm; 300 %
Application temperature	+5°C recommended, can be used from -10°C
Temperature resistance	-30°C to +100°C
Initial tack	excellent
Condensation resistance	good
Aging resistance	Very good
Storage life	24 months after production date
Storage	in the original package at room temperature

* Refers to the Central European climate

** measured in accordance with the standards in force for the testing of adhesive tapes

For your information

The length tolerances of the foils are according to DIN 7715. Width tolerances :+/- 2.50 mm.

Note

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 08-2017

The producer reserves the right to make changes. 2020 04 01