

Product

A manually tearable LDPE film with a synthetic rubber adhesive layer.



Application examples

- professional building industry
- on irregular surfaces
- indoor and outdoor applications

Colour

grey

Thickness

190 µm

Widths

30-35-40-45-50-55-60-65-70-75-80-85-90-95-100-105-110-115-120-125-130-135- ... 1.000 mm

Length

50 meter

Packaging

On a roll

In boxes, separated by a silicone paper

Advantages

- ✓ good aging resistance
- ✓ good temperature resistance
- ✓ good adhesion on smooth, dirty, dusty as well as rough surfaces
- ✓ good adhesion to stone, concrete, wood and certain types of plastic
- ✓ manually tearable
- ✓ relatively good moisture resistance
- ✓ avoid prolonged contact with UV

Remark

The materials and substrate must be rease-free and solid.

Technical properties

Property	Value + unit
Adhesive carrier	LDPE film + polyester tissue
Adhesive	synthetic rubber (hotmelt)
Total thickness	190 µm
Adhesion on steel	17,50 N/25 mm
Tensile strength	95 N/25 mm
Tissue density	26 mesh
Steel ball test	3 cm
Temperature resistance	van -15°C tot +60°C
UV resistance	matig
Storage life	12 months after production date
Storage	in its original packaging at 21°C and 50% relative humidity

For your information

The length tolerances of the foils are according to DIN 7715. Width tolerances :+/- 2.50 mm.

Note

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 01-2015

The producer reserves the right to make changes. 2020 04 01