

Product

Low density (LDPE) polyester tape with a very strong acrylic adhesive layer on one side.

Application examples

- airtight connections between vapour retardant or vapour regulating (interior) films
- airtight finish between elements in timber frame construction (e.g. OSB, ...)
- airtight connection of the vapour barrier to a wooden surface
- airtight (interior) finishing around joinery (between the wooden or pvc profiles and the wooden structure)
- taping of cracks between specific insulating plates

Colour

Green

Thickness

0,28 mm (without protective foil)

Widths

30 to 1.500 mm (every 5 mm)

Length

25 meter

Packaging

On a roll

In boxes, separated by a silicone paper

Protection of the adhesive

Siliconized paper

Advantages

- ✓ excellent aging resistance
- ✓ very good resistance to moisture
- ✓ can already be used from +5°C (dry surface)
- ✓ solvent-free adhesive layer

Remark

The materials and substrate must be dry, grease-free, oil-free, solid and dust-free.



Technical properties

Property	Value + unit
Adhesive carrier	LDPE-film
Adhesive layer	solvent-free, modified water-based acrylate
Weight (without protective foil)	210 gr/m ²
Adhesion (DIN EN 1939)	± 35 N/25 mm
Aging resistance	excellent
Resistance to moisture	Very good
Temperature resistance (test AA-B-12-07)	-40°C to +100°C
UV resistance	3 months
Final adhesion	1 hour
Storage	At 15° to 25°C and 40% to 60% relative humidity

For your information

The length tolerances of the foils are according to DIN 7715. Width tolerances :+/- 2.50 mm.

Note

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 10-2014

The producer reserves the right to make changes. 2020 04 01