



Product

Round, open-cell polyurethane foam.

Application examples

- non-load-bearing joints
- mechanical joints (walking joints) or joints subjected to pressure (joints underwater)
- in order to obtain the correct joint depth
- draught sealing

Colour

Grey

Diameters and packaging

| Diameter (mm) | Packaging |
|---------------|-----------|
| 10 | 500 x 1 m |
| 15 | 250 x 1 m |
| 20 | 200 x 1 m |
| 25 | 100 x 1 m |
| 30 | 100 x 1 m |
| 35 | 50 x 1 m |
| 40 | 50 x 1 m |
| 50 | 50 x 1 m |
| 70 | 25 x 1 m |

Versions

In strips

Length

one (1) meter

Properties PU

- ✓ sound absorbing
- ✓ can be compressed

Technical properties

| Property | Value + unit |
|------------------------|---|
| Density | 22 to 40 kg/m ² |
| Structure | Open-cell |
| Temperature resistance | -25°C to +80°C |
| Compressibility | 90% |
| Elongation at break | 180% |
| Tensile strength | 100 kPa |
| Permeability | water, air and gas |
| Storage | in the original, unopened packaging at room temperature |

General information

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 01-2007

The producer reserves the right to make changes. 2020 04 01