



Product

BUTYL CS-24 is a high-quality rubber-coated sealant with excellent adhesion to most building surfaces. BUTYL CS-24 cures by releasing the solvent. The product is intended for use in enclosed, non-porous filler joints.

If the surface of the sealant is exposed to weather conditions, BUTYL CS-24 cures 3 to 5 days after application, depending on the temperature, due to solvent loss and forms a flexible rubber seal. BUTYL CS-24 is mainly intended for filling applications.

Application examples

- Durable air and watertight sealing between overlapping metal sheets
- air sealing of curtain walls, pipe seals, panels in vehicles and caravans, profiled roof panels
- remains flexible at low temperatures and can therefore be used to seal cold areas.

Colour

black

Packaging

Cartridges of 310 ml / 25 cartridges per box

Advantages

- ✓ service life of 20 years in recommended applications
- ✓ no stains
- ✓ no oil spills
- ✓ very flexible / no hardening at low temperatures
- ✓ excellent adhesion
- ✓ little shrinkage

Restrictions

- not suitable for use at constant immersion in water
- do not use with open joints
- do not use in contact with the edge of laminated glass or insulating glass units

Instructions for use

All surfaces must be clean and dry and free of dirt, dust, grease and other contaminants. BUTYL CS-24 should be applied with a sealant gun, firmly to the surface to ensure good contact and adhesion.

Technical properties

Property	Value + unit
Specific weight	1.58-1.63 g/cm ³
Flash point	>55°C
Application temperature	+5°C to +40°C
Temperature resistance	-30°C to +80°C
Flow (ISO 7390)	no flow
Longevity	at least 20 years if used as recommended
Storage	store in a cool and dry place
Shelf life	12 months in unopened packaging, if stored in cool, dry conditions

Instructions for use (continued)

After application, do not wait too long before joining and mechanically fixing the surfaces.

Sealant removed from the joint can be wiped off and the surface cleaned with white spirit.

Health and Safety

BUTYL CS-24 is flammable and contains organic solvent. Keep away from sources of ignition. Use in well-ventilated areas.

If BUTYL CS-24 comes into contact with the eyes, rinse eyes abundantly with clean water. Seek medical advice if irritation persists. If BUTYL CS-24 is ingested accidentally, seek medical advice and show the package or label. In case of eye contact, rinse eyes with plenty of warm water and seek medical advice. Refer to the Health and Safety Data Sheet for further information.

Keep out of reach of children and animals.

General information

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 2011 06

The producer reserves the right to make changes. 2020 04 01