

Product

Adhesion promotor for the use of various products on porous, damp substrates or in the case of use at temperatures between -10°C and +5°C.

Application examples

Especially developed as an adhesion improver in facades, on porous, damp substrates:

CS-EPDM Foil adhesives:

CS-EPDM Mastic Bond FA
CS-EPDM Contact Bond TA

Novoproof range self-adhesive EPDM:

CS-EPDM Foil ZK
CS-EPDM Easy Foil
CS-EPDM Foil with HTB adhesives

Castelein Easy Foils:

Easy Foil OS Black
Easy Foil ST
Easy Foil SI
Easy Foil Dynamic
Easy Foil N

Various Castelein products with adhesive based on butyl or acrylate

As a barrier between EPDM and the Castelein Easy Foil range (prevents migration of plasticisers into EPDM).

Colour

black

Packaging

4.5 kg kettle

Consumption

10-15 gr/ meter on 5 cm

Remark

Always use a hard pressure roller for optimal adhesion. Two types are available: hard silicone rubber or steel.



Membrane n°
22003 Classe: A-B-C
22012 Classe: B-C
22015 Classe: C

Technical properties

Property	Value + unit
Base	synthetic rubber with solvents
Density	0,835 kg/l
Dry solids	36,30 %
Application temperature	-10°C to +35°C
Temperature resistance	-40°C to +90°C
Flashpoint	-20°C
Brookfield viscosity	900 mPa.s +/- 100
Certificates	ATG 3288
Shelf Life	18 months after production date
Storage	dry in unopened package at room temperature

Application

Stir well before use and distribute evenly with paint brush or paint roller. After 5 to 15 minutes check that it is finger-dry. This surface can remain uncovered for several hours if no dirt or moisture deposits on the surface.

General information

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Information about the SNJF Label and the Guidelines can be found at www.oc-sjff.fr.

Technical data of supplier: 02 2022

The producer reserves the right to make changes. 2025 07 01