

Product

Elastomeric membrane obtained by combining EPDM (Ethylene Propylene Diene Monomer) with oils and fillers followed by calendaring and vulcanization.

Application examples

- against rising moisture
- water barrier at the base of the cavity wall
- flood barrier under thresholds
- around curtain walls
- in steel facades
- renovation of gutters
- external facade insulation
- around frames/around windows

Colour

Black

Thickness

1,00 mm (-5% / +10%)

Widths

100-110-120-130-140-150-160-170-180-190-200-210-220-230-240-250-260-270-280-290-300-... - 1.500 mm

Length

25 meter

The length might fluctuate \pm 5% due to the elasticity of the material.

Available versions

With 1 or 2 acrylic adhesive strips

Without adhesive strips

Properties

- ✓ very good resistance to weather conditions, UV and aging
- ✓ very good long-term watertightness
- ✓ highly elastic and putrefaction resistant
- ✓ recyclable
- ✓ solvent-free

Adhesive sealant EPDM FOIL BOND

A one component adhesive sealant made of MS Polymer.

Colour: black

Especially developed for bonding and sealing CS-EPDM Structure Foil to most common building materials such as aluminium (untreated, anodised, powder coated), mineral substrates (concrete, stone, clinker, plaster), PVC windows, steel (galvanised, powder coated), wood (pre-testing), overlaps between EPDM films. Aluminium sausages of 600 ml.



Technical properties membrane

Property	Value + unit
Reaction to fire (EN 13501-1)	E
Watertightness (2 kPa) (EN 1928)	Pass
Water vapour permeability (μ) (EN 1931)	50.000
Impact resistance (EN 12691)	NPD
Joint shear resistance (EN 12316-2)	NPD
Tensile strength (EN 12311-2)	\geq 8 MPa
Elongation (EN 12311-2)	\geq 300 %
Tear resistance (EN 12310-2)	\geq 20 N
Durability against ageing (EN 1296/EN 1931)	Pass

Harmonised technical specification EN 13984:2013

Application

Press very well with a pressure roller

Maintain the roof tile principle



Versions and accessories



CS-EPDM STRUCTURE FOIL

1,00 MM

Accessories

NOVOPROOF® Primer

Adhesion promoter for using the Kleber TA contact adhesive or the Kleber FA adhesive sealant on a porous, damp substrate or when applied at temperatures between +3°C and -10°C.

NOVOPROOF® Kleber TA

Contact adhesive based on synthetic rubber used for adhesion of the foil on all types of surfaces (wood, aluminium and stone).

NOVOPROOF® Cleaner

To clean the EPDM (if not clean enough) before bonding with the adhesive sealant FA or the contact adhesive Kleber TA.

Note

The information contained in this document is provided in good faith and is believed to be correct. However, we have no influence on the conditions in which these products are used or the methods by which they are used. Therefore, this information is not a substitute for tests which the customer must perform himself/herself in order to ensure that the products are safe, effective and achieve the intended purposes. Suggestions regarding the use of the product must not be used as grounds for infringement of any patent whatsoever. The only guarantee Castelein Sealants offers is that this product complies with the Castelein Sealants terms and conditions of sale in force at the time of shipment. Your only remedy in the event of a breach of this guarantee is the refund of the purchase price or the replacement of the product that does not comply with the guarantee.

Technical data of supplier: 07-2022

The producer reserves the right to make changes. 2022 07 25